



## Insulclamp

Channel clip ideal for bigger commercial air conditioning and refrigeration installations.



Channel





## **Key Features**

• Easy installation into 40mm x 40mm and 40mm x 20mm channel

**SIZING OPTIONS** 

Part No.

(Plastic Bag)

B6268

B6274

B6267

B6276

B6273

B6277

B6264

B6265

B6266

B6269

B6270

B6271

B6272

B6275

Pack Qty

(Plastic Bag)

10

10

10

10

10

10

10

10

10

5

5

5 5

Height Above Channel (mm)

32

35

38

41

44

47

54

60

76

92

98

117

130

143

- Insulates against heat loss and reduces vibration
- Quick to install with lock nuts

Max.

Unsupported Span (m)

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

• Fits into shallow void

Size

1/4"

3/8"

1/2"

5/8"

3/4"

7/8"

11/8"

13/8"

1<sup>5</sup>/8"

21/8"

25/8"

31/8"

35/8"

41/8"

- Supports individual pipes into a thermo-rubber cushion between two metal plates
- Thermo-rubber cushion insert withstands maximum temperature of 130°C (zinc bracket 1000°C)


SPECIFICATIONS	
Materials of construction	Zinc passivated steel with rubber cushion
Max. temp	130°C
Max. rec. distance per clip	1.2m


OTHER PROPERTIES	
Thermal conductivity	K = 0.27 W/m/°C
















Information correct at time of going to press. Not all products are available in all regions.